WBW Wash Down Scales





Ideal for food preparation, food processing plants, agricultural facilities, and more, WBW scales feature IP65 rated wash down housing and a large stainless steel weighing pan. Colour indicators for Under, Ok, and Over limits make check weighing fast and easy, and a brilliant backlit LCD with capacity tracker, indicators for overloads, low battery, and auto power-off, make the WBW very user friendly. They operate with an AC adaptor or rechargeable battery pack for portability; both are included.









WBW Highlights:

Check weighing product is faster than ever with the WBW's colour coded LED indicators. Amber, green and red LED's quickly show you if an item is within acceptable limits, over, or under, without looking at the actual weight

An easy-to-read backlit LCD with capacity tracker shows capacity usage as well as the weight. The capacity tracker helps prevent users from exceeding the scale's capacity when adding ingredients or making up batches.

WBW scales can be moved to where they are needed thanks to the internal rechargeable battery pack. And the vertical front panel makes them easy to read and operate on a counter, table or bench.

IP65 for wash down environments, included extensive sealing both inside and out to give a high level of protection for those wet applications. Advanced overload protection helps protect the scale from overloads and shock loading

WBW...designed for food, agriculture, and other wash down applications.

Features

- Backlit LCD with capacity tracker
- Coloured LED check limit indicators
- Rechargeable battery and AC adaptor included
- · Stainless steel pan
- Weighs in grams, kilograms, pounds and ounces
- Optional rear display
- IP65 rated for wash down
- Overload protection

Applications

- Weighing
- Check weighing
- Wash down







Advanced overload protection

Technical Specifications

Model	WBW 2	WBW 4	WBW 8	WBW 16
Capacity	2000g	4000g	8000g	16kg
Readability	0.2g	0.5g	1g	2g
Repeatability	0.1g	0.2g	0.5g	1g
Linearity	0.2g	0.4g	1g	2g
Pan Size	210mm x 173mm			
Weighing Units	kg, g, lb,oz			
Applications	Weighing, check weighing			
Stabilisation Time	2 seconds typical			
Operating Temperature	-10° to 40°C			
Power Supply	AC adapter, internal rechargeable battery (both included)			
Calibration	Automatic External			
Display	6 digits backlit LCD digital display (optional rear display available)			
Housing	IP65 (only when used on battery) sealed ABS plastic housing with stainless steel pan			
Net Weight	3.3kg			
Approvals	Non approved			
Overall Dimensions	231mm x 265mm x 153mm			

Accessories

Item No. 6340 - Rear Display (factory fitted only)